

TRAILER

SPECIFICATIONS

| | | |
|---------------------|---------------------|-----------------------|
| Length | 53' | 16.15 m |
| Width | 8' 2" | 2.49 m |
| Height | 13' 5" | 4.09 m |
| Cargo Space | 38' x 4' 6" x 7' 4" | 11.60 x 1.40 x 2.20 m |
| Storage Compartment | 10" x 13" x 42" | 0.25 x 0.33 x 1.10 m |
| Cargo Capacity | 5000 lb | 2268 kg |
| Weight | 42100 lb | 19100 kg |

STAGE FLOOR

| | | |
|---|------------------------|-----------------------|
| Length and Depth | 40' x 39' 2" | 12.20 x 11.94 m |
| Length and Depth with Extension Platforms | 64' x 39' 2" | 19.51 x 11.94 m |
| Height from Ground | 3' 6" to 6' | 1.07 to 1.83 m |
| Design Live Load | 100 lb/ft ² | 490 kg/m ² |
| Type of Surface | Plywood on steel | |

ROOF

| | | |
|--|----------------------------|-----------------------|
| Length and Depth | 42' 4" x 40' 9" | 12.91 x 12.43 m |
| Clearance (Inclined roof) | 22' 9" to 25' 5" | 6.93 to 7.76 m |
| Maximum Height from Banners | 32' 4" | 9.86 m |
| Type of Surface | Fibreglass bonded on steel | |
| Load Bearing Capacity † | 26000 lb | 11793 kg |
| 4 Rigging Points | 2000 lb each | 907 kg each |
| 12 Rigging Points | 1000 lb each | 454 kg each |
| 8 Rigging Points | 500 lb each | 227 kg each |
| 2 Trusses - Central Roof (T1) | 3000 lb each | 1360 kg each |
| 2 Trusses - Downstage and Upstage (T2) | 2000 lb each | 907 kg each |
| 2 Lateral Overhang Rigging Points | 2000 lb each at 6' | 907 kg each at 1.83 m |
| 2 Bi-directional Rigging Beams * | 4000 lb | 1814 kg |

PRACTICAL ASPECTS

| | |
|---|--|
| Installation Time once Levelling Complete | 2.5 Hours - Less without windwalls |
| Personnel Required | 1 Certified technician and 3 stagehands |
| Site Preparation | None |
| Heavy Machinery Required | None |
| Mode of Transportation | 1 Fifth-wheel tractor |
| Gust Wind Resistance | 60 mph (97 km/h) with windwall or 90 mph (145 km/h) without windwall |
| Promotional Visibility * | Rolling billboard or multiple banner options |
| Windwalls * | Weatherproof, fire-retardant vinyl or scrim (blow-through material) |
| Vertical Banner Supports * | Quick to install - Offers close to 834 sqft. (77.5 m) of promotional space |
| Floor Extension Platforms * | Integrated brackets - easy to install |

Values indicated are nominal. Due to STAGELINE'S product improvement policy, technical specifications may change without notice.

† Please refer to rigging plan.

* Offered in option.

450 589-1063

Fax: 450 589-1711

1-800-267-8243 in N.A.

info@stageline.com

www.stageline.com