

	Imperial	Metric
Trailer		
Length	46' 3"	14.10 m
Width	8' 2'	2.49 m
Height	13' 2"	4.01 m
Cargo Space	31' 7" x 5' 8" x 7' 8"	9.64 x 1.75 x 2.35 m
Storage Compartment	10" x 13" x 3' 7"	0.25 x 0.33 x 1.10 m
Cargo Capacity	10000 lb	4536 kg
Weight	29400 lb	13335 kg
Floor		
Type of Surface	Plywood on steel	
Length x Depth	32' x 24'	9.75 x 7.32 m
Height from Ground	3' 6" to 5' 3"	1.07 to 1.60 m
Capacity	100 lb/sq ft	490 kg/m ²
Roof		
Type of Surface	Fiberglass Bonded on Steel	
Length x Depth	34' 5" x 27' 7"	10.50 x 8.41 m
Downstage T2 Truss	19' 1"	5.62 m

^t Refer to Rigging Plan

1.4 Standard Features

Standard Features		Imperial	Metric
Roof Structure			
6	Built-in Rigging Points	1000 lb each	454 kg each
4	Rigging Pipes - 9.53 m (31'3")	30 lb per lin. ft	45 kg per lin. m
2	Trusses in central roof	2000 lb each or 30 lb/lin. ft	908 kg each or 45 kg/lin. m
1	Front Overhang Truss	2000 lb each	908 kg each
1	Rear Overhang Truss	2000 lb each	908 kg each
2	Front Overhang Pipes - 2.4 m (8')	350 lb each at 3'	159 kg each at 0.93 m
2	Front Overhang Pipes - 1.4 m (4'9")	750 lb each at 3'	340 kg each at 0.93 m
2	Lateral Overhang Rigging Beams	up to 2500 lb each	up to 1134 kg each
4	Steel Corner Posts		
	FRP	34' 5" x 27' 7"	10.5 x 8.4 m
Hydraulics			
	Maximum Load Lifting Capacity	12000 lb	5443 kg
	Maximum Load Bearing Capacity	18500 lb	8391 kg
	Double Wast Lifting Mechanism		
	High Power Hydraulic System		
4	Levelling Hydraulic Stabilizers	up to 5' 3"	up to 1.6 m
1	Kohler 7 hp Gas Engine		
Stage			
1	Stage Deck / quick-levelling legs	32' x 24'	9.75 x 7.32 m
2	Embedded Floor Panels		
1	28-inch Adjustable Stairway		
1	500 W Quartz Work Lights		
Trailer			
1	Hydraulic Gooseneck		
	Air Suspension		
8	Tires 17.5 - ABS Air Brakes		
1	Storage Compartment.	10" x 13" x 3' 7"	25 x .33 x 1.1 m
1	Spare Wheel with Storage		
1	Cargo Bumpers / Cargo Capacity	10000 lb	4536 kg

	Options	Imperial	Metric
	Upstage Fire-retardant Windwall	32' x 28'	9.75 x 8.53 m
	Skirting - Front and Downstage Side		
	Stage Guardrails		
	5 or 7 Roof Banner Supports	4'	1.22 m
	Side Banner Supports	12'	3.66 m
	Side Banner Retaining Bars		
	Floor Extension Platforms with Accessories	4' x 8'	1.22 x 2.43 m
	Floor Extension Guardrails		
	Line Array Rigging Beam		
	Roof Canopy - Stagefront and Stagerear		
	Stage Reversibility		
	Screen Support		
	Loading Ramp	3' x 12'	0.91 x 3.66 m
	Electric Motor, 1 hp		
	Downstage fire-retardant Windwall		

1.6 Supplied Spare Parts and Tools

- 1 Level
- 1 Kohler Maintenance Manual
- 1 Rubber and windwalls repair samples
- 2 Strap Ratchets 1"
- 2 Strap Ratchets 1 3/4"

We recommend that you purchase the following items: 20' (6 m) step ladder, structure punch, vise-grip pliers, and a multi-bit screwdriver.

1.7 Registration Certificate and Lock Keys

The container holding the trailer registration certificate and compartment keys is located on the stage structure behind and to the left of front stabilizers and gooseneck levers.

